



HP Lubricants - Product Data Sheet



HP TRIMOFIN 55

STAINING EP TYPE STRAIGHT CUTTING OIL CONTAINING ACTIVE SULPHUR AND CHLORINE FORTIFIED WITH OILINESS ADDITIVES POSSESSING MEDIUM VISCOSITY.

APPLICATION AREAS :

MEDIUM VISCOSITY OIL SPECIALLY DEVELOPED FOR HEAVY DUTY APPLICATIONS LIKE GEAR HOBGING, THREAD CUTTING ETC. THE OIL IS ALSO SUITABLE FOR ALL MACHINING OPERATIONS ON HIGH TENSILE STEELS AND FOR LESS SEVERE OPERATIONS ON STAINLESS AND SHEAR RESISTANT ALLOYS.

PROPERTIES	HP TRIMOFIN 55
KINEMATIC VISCOSITY @ 40 deg C,cSt	32-42
FLASH POINT deg C, COC, MIN	160
SAPONIFICATION VALUE, mg KOH/gm	-
COLOUR, ASTM, DILUTE,MAX	8
CONTAINS	
INACTIVE SULPHUR	NO
ACTIVE SULPHUR	YES
CHLORINE	YES

PERFORMANCE BENEFITS :

EXCELLENT HEAT REMOVAL PROPERTIES
EXCELLENT EP PROPERTIES
SUPERIOR WETTABILITY

CONT...

FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST
REGIONAL OFFICE