



# HP Lubricants - Product Data Sheet



## HP TRIMOFIN 56

STAINING EP TYPE STRAIGHT CUTTING OIL CONTAINING ACTIVE SULPHUR AND CHLORINE FORTIFIED WITH OILINESS ADDITIVES POSSESSING MEDIUM VISCOSITY WITH HIGHLY POTENT EP ADDITIVE PACKAGE.

### APPLICATION AREAS :

MEDIUM VISCOSITY OIL SUITABLE FOR HEAVY DUTY APPLICATIONS SUCH AS THREADING, BROACHING, TAPPING ETC ON FERROUS METALS.

<b>PROPERTIES</b>	<b>HP TRIMOFIN 56</b>
<b>KINEMATIC VISCOSITY @ 40 deg C,cSt</b>	<b>32-45</b>
<b>FLASH POINT deg C, COC, MIN</b>	<b>160</b>
<b>SAPONIFICATION VALUE, mg KOH/gm</b>	<b>-</b>
<b>COLOUR, ASTM, DILUTE,MAX</b>	<b>8</b>
<b>CONTAINS</b>	
<b>INACTIVE SULPHUR</b>	<b>YES</b>
<b>ACTIVE SULPHUR</b>	<b>YES</b>
<b>CHLORINE</b>	<b>YES</b>

### PERFORMANCE BENEFITS :

EXCELLENT HEAT REMOVAL PROPERTIES  
EXCELLENT EP PROPERTIES  
SUPERIOR WETTABILITY  
IMPROVED FINISH  
INCREASED TOOL LIFE

**CONT...**

FOR FURTHER INFORMATION PLEASE CONTACT OUR NEAREST  
REGIONAL OFFICE