



LUBRICANTS™

POWER TO PERFORM™

HYCOM 150 P

COMPRESSOR OILS

SPECIAL FEATURES

It is blended out of highly refined turbine base stocks and special types of anti-oxidants, anti-rust, antifoam and demulsifier which do not react to any of the types of gases.

PERFORMANCE BENEFITS

This oil has good demulsibility property, low deposits and sludge foaming tendency at a wide range of working temperature and in any gaseous atmosphere.

Meets DIN 51506 VDL specifications, IS 13256:1992 DAB

APPLICATION AREA

Specially developed for railway compressors.

PHYSICO-CHEMICAL PROPERTIES

Appearance	Clear
Acidity, Total mg KOH / g	0.20
Density @ 29.5°C, g/cc	0.8770
Flash Point, COC, °C	>210
Pour Point, °C	<-15
OXIDATION STABILITY @ 135°C, 168 Hrs	Pass
FZG Rig Test, Pass Load Stage	>8
Rusting Test, Syn Sea Water, 24 Hrs	Pass
Kin. Viscosity @ 40°C, cSt	135-165
Kin. Viscosity @ 100°C, cSt	15.0
Viscosity Index	100

AUTHORISED CFA / ILD / LD

PANVEL INDUSTRIAL FASTNERS PVT LTD

Plot No 29 to 33 & 37, Jawahar Co-operative Industrial Estate, Kamothe, Navi Mumbai - 410209

Contact - 022-27431702 / 9821137735 , panvelcfa_hpcl@rediffmail.com