



LUBRICANTS™

POWER TO PERFORM™

HYCOM C 100, 150, 220, 320, 460 COMPRESSOR OILS

SPECIAL FEATURES

These are compressor oils formulated with selected base stocks and a special compounding agent to give excellent resistance to washing effect of water. These are further fortified with anti-rust and anti-corrosion agent and have good fluidity at low temperature.

HYCOM C grades meet DIN 51506.

APPLICATION AREA

HYCOM C grades are recommended for cylinder lubrication of single and multistage air compressors with moist air and provide excellent lubrication of piston rings, valves, cylinder liners etc. HYCOM C 460 has low sulphur content for applications in ammonia synthesis compressors in fertiliser plants.

PHYSICO-CHEMICAL PROPERTIES

	HYCOM C			
	100	150	220	320
Kinematic Viscosity @ 40°C, cSt	95 – 105	140 – 160	210 – 230	310 – 330
Flash Point, COC, °C, Min.	190	210	240	248
Saponification number, mg KOH/g	2.5-5.0	2.5-5.0	2.5-5.0	7-10
Pour Point, °C, Max	(-)6	0	3	6

AUTHORISED CFA / ILD / LD

PANVEL INDUSTRIAL FASTNERS PVT LTD

Plot No 29 to 33 & 37, Jawahar Co-operative Industrial Estate, Kamothe, Navi Mumbai - 410209

Contact - 022-27431702 / 9821137735 , panvelcfa_hpcl@rediffmail.com